NUMERICAL SOLUTION OF FREE SURFACE, POROUS
FLOW PROBLEMS

by

V. Casulli* and D. Greenspan
Department of Mathematics
University of Texas at Arlington
Arlington, Texas 76019

Technical Report No. 146

January, 1981

*Permanent address:

Istituto per le Applicazioni del Calcolo
viale del Policlinico, 137
Roma, Italia 00161

ABSTRACT

In this paper an inexpensive, fast numerical method is developed for the approximate solution of general, free surface, porous flow problems. The method is so designed that the required numerical boundary conditions coincide exactly with the required physical boundary conditions. Numerical examples of a prototype problem are described and discussed.

1. Introduction. Porous flow is of interest, for example, to mathematicians, geologists, ecologists, civil engineers and fluid dynamicists (see, e.g., refs. [1], [9], [11] and the numerous additional references contained therein). Models are usually [11], but not always [8], formulated in terms of classical continuum mechanics, with equations of motion often being highly nonlinear. Related problems are further complicated by the presence of a free boundary, and most modern computer methodology has been applicable only under highly restrictive assumptions [5], [7], [10], [11], [13].

In this paper we will develop a method for general, continuum formulated, free surface, porous flow problems. The method is analogous to that developed recently by Casulli [3], who showed that combining the Los Alamos MAC method for Navier-Stokes problems [10], [13] with the Courant-Isaacson-Rees method for hyperbolic systems [6] leads to a new method which is more powerful than either of its constituents. This new method does not require artificial viscosity for stability, applies for all Reynolds numbers, and allows for thermal, nonhomogeneous, and three dimensional considerations.

2. Governing Equations. For simplicity only, let us consider the flow of a homogeneous fluid in a porous medium. The governing three dimensional equations are derived from the principles of conservation of momentum and mass, and are given as follows [14]. The generalized Darcy's equation of motion is

$$(1) \quad \frac{1}{\eta} \frac{Du_1}{Dt} = -\frac{\partial \phi}{\partial x_1} + X_1 - \frac{\nu}{k} u_1 ,$$

where η is the porosity of the medium, $\vec{u}$ is the seepage fluid velocity, ϕ is the ratio of pressure to the constant density of the fluid, $\vec{X}$ is a body force, ν is the kinematic viscosity coefficient, and k is the permeability of the medium. The equation of continuity for an incompressible fluid is

$$(2) \quad \frac{\partial u_\alpha}{\partial x_\alpha} = 0 ,$$

where, as usual, repetition of indices denotes summation. For any free surface which can be represented as a single valued function $x_3 = h(x_1, x_2, t)$ the change in surface elevation is determined [11] by the kinematic condition

$$(3) \quad \eta_s \frac{\partial h}{\partial t} + u_{1,s} \frac{\partial h}{\partial x_1} + u_{2,s} \frac{\partial h}{\partial x_2} = u_{3,s} ,$$

where η_s is the porosity of the medium at the free surface, and where $\vec{u}_s$ is the seepage velocity at the fluid surface.

The governing two dimensional equations for the models most often considered can now be derived from system (1)-(3) as follows. The temporal acceleration in (1) has to be included in unsteady flow problems. However, the convective acceleration in (1) is relatively insignificant and can be neglected. Thus, in the usual notation, we arrive at

$$(4) \begin{cases} \frac{\partial u}{\partial t} = -\eta \frac{\partial \phi}{\partial x} - \frac{\eta y}{k} u \\ \frac{\partial v}{\partial t} = -\eta \frac{\partial \phi}{\partial y} - \frac{\eta y}{k} v - g\eta \\ \frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} = 0 \end{cases}$$

with the free surface equation

$$(5) \quad \eta_s \frac{\partial h}{\partial t} + u_s \frac{\partial h}{\partial x} = v_s .$$

In applying (4) and (5), the following initial conditions are employed:

$$(6) \quad \begin{cases} u(x, y, t_0) = u_0(x, y) \\ v(x, y, t_0) = v_0(x, y) \\ h(x, t_0) = h_0(x) \end{cases} .$$

The boundary conditions for (4) are given by assigning either the pressure ϕ_s or the normal velocity $u_{\perp}$ as a function of time on the boundary. In particular, at the free surface the pressure is zero at all times, while at the impenetrable boundaries the normal velocity is zero.

The free surface equation (5) needs one boundary condition at the point of intersection with the fixed boundary only if the fixed boundary is an inflow boundary at such a point [2]. In the case the surface height $h(x, t)$ must be specified at this point as a function of time.

Further consideration about boundary conditions will be given in Section 5.

3. Difference Approximations for the Equations of Motion. Our finite approximations for system (4) are based on the MAC (Marker and-Cell) method [10] , [13] and can be extended, if desired, in a direct way to system (1)-(2). Specifically, the finite difference mesh consists of rectangular cells of width Δx and height Δy . The field variables u , v and ϕ are defined at the locations shown in Figure 1: the u component of velocity is defined at the center of each vertical side of a cell, the v component of velocity at the center of each horizontal side, and the pressure ϕ at each cell center.

FIGURE 1. Positions of field variables.

The finite difference equations corresponding to the first two equations of system (4), that is, to Darcy's equations, are

$$(7) \begin{cases} u_{1+\frac{1}{2},j}^{n+1} = u_{1+\frac{1}{2},j}^n - \Delta t \left[\eta_{1+\frac{1}{2},j} \frac{\phi_{1+1,j}^{n+\frac{1}{2}} - \phi_{1,j}^{n+\frac{1}{2}}}{\Delta x} + \left(\frac{\eta \nu}{k} \right)_{1+\frac{1}{2},j} u_{1+\frac{1}{2},j}^n \right] \\ v_{1,j+\frac{1}{2}}^{n+1} = v_{1,j+\frac{1}{2}}^n - \Delta t \left[\eta_{1,j+\frac{1}{2}} \frac{\phi_{1,j+1}^{n+\frac{1}{2}} - \phi_{1,j}^{n+\frac{1}{2}}}{\Delta y} + \left(\frac{\eta \nu}{k} \right)_{1,j+\frac{1}{2}} v_{1,j+\frac{1}{2}}^n + g \eta_{1,j+\frac{1}{2}} \right]. \end{cases}$$

Of course, implementation of (7) requires first the determination of the pressure field $\phi_{1,j}^{n+\frac{1}{2}}$, which is accomplished as follows.

The finite difference equation corresponding to the last equation of system (4), that is, the incompressibility condition, in each cell is given by

$$(8) \quad \frac{u_{1+\frac{1}{2},j}^{n+1} - u_{1-\frac{1}{2},j}^{n+1}}{\Delta x} + \frac{v_{1,j+\frac{1}{2}}^{n+1} - v_{1,j-\frac{1}{2}}^{n+1}}{\Delta y} = 0.$$

As in [3], the pressure field $\phi_{1,j}^{n+\frac{1}{2}}$ at the center of each cell must be computed in such a way that the discrete incompressibility condition (8) is valid throughout. To find a difference equation for the pressure, we require that the seepage velocity components computed with (7) satisfy (8). We first define

$$F_{1+\frac{1}{2},j}^n = \left[1 - \Delta t \left(\frac{\eta \nu}{k} \right)_{1+\frac{1}{2},j} \right] u_{1+\frac{1}{2},j}^n$$

$$G_{1,j+\frac{1}{2}}^n = \left[1 - \Delta t \left(\frac{\eta \nu}{k} \right)_{1,j+\frac{1}{2}} \right] v_{1,j+\frac{1}{2}}^n - (\Delta t) g \eta_{1,j+\frac{1}{2}},$$

so that (7) become

$$(9) \quad \begin{cases} u_{i+\frac{1}{2},j}^{n+1} = F_{i+\frac{1}{2},j}^n - (\Delta t) \eta_{i+\frac{1}{2},j} \frac{\phi_{i+1,j}^{n+\frac{1}{2}} - \phi_{i,j}^{n+\frac{1}{2}}}{\Delta x} \\ v_{i,j+\frac{1}{2}}^{n+1} = G_{i,j+\frac{1}{2}}^n - (\Delta t) \eta_{i,j+\frac{1}{2}} \frac{\phi_{i,j+1}^{n+\frac{1}{2}} - \phi_{i,j}^{n+\frac{1}{2}}}{\Delta y} \end{cases} .$$

Substitution of (9) into (8) yields the following finite difference equation for pressure:

$$(10) \quad \eta_{i+\frac{1}{2},j} \frac{\phi_{i+1,j}^{n+\frac{1}{2}} - \phi_{i,j}^{n+\frac{1}{2}}}{(\Delta x)^2} - \eta_{i-\frac{1}{2},j} \frac{\phi_{i,j}^{n+\frac{1}{2}} - \phi_{i-1,j}^{n+\frac{1}{2}}}{(\Delta x)^2} \\ + \eta_{i,j+\frac{1}{2}} \frac{\phi_{i,j+1}^{n+\frac{1}{2}} - \phi_{i,j}^{n+\frac{1}{2}}}{(\Delta y)^2} - \eta_{i,j-\frac{1}{2}} \frac{\phi_{i,j}^{n+\frac{1}{2}} - \phi_{i,j-1}^{n+\frac{1}{2}}}{(\Delta y)^2} \\ = \frac{F_{i+\frac{1}{2},j}^n - F_{i-\frac{1}{2},j}^n}{(\Delta t)(\Delta x)} + \frac{G_{i,j+\frac{1}{2}}^n - G_{i,j-\frac{1}{2}}^n}{(\Delta t)(\Delta y)} .$$

Equation (10) is then solved at each time step by an iteration (see, e.g., [3]) that adjusts the velocities through changes in the pressure field.

Note that for constant porosity η , equation (10) reduces to a finite difference Poisson equation.

4. Approximation of Free Surface Motion. A finite difference scheme which discretizes the free surface equation (5) and simultaneously allows for the correct physical boundary

conditions [2] is the Courant, Isaacson and Rees method, which is implemented as follows. The surface height $h_{i+\frac{1}{2}}^n$ is defined on each vertical grid line and the equation (5) is approximated by

$$(11) \quad h_{i+\frac{1}{2}}^{n+1} = h_{i+\frac{1}{2}}^n + \frac{\Delta t}{\eta_{s,i+\frac{1}{2}}} \left[v_s^n - u_s^n \frac{\Delta h_{i+\frac{1}{2}}^n}{\Delta x} \right],$$

where

$$\Delta h_{i+\frac{1}{2}}^n = h_{i+\frac{1}{2}}^n - h_{i-\frac{1}{2}}^n, \quad \text{if } u_s^n \geq 0$$

$$\Delta h_{i+\frac{1}{2}}^n = h_{i+(3/2)}^n - h_{i+\frac{1}{2}}^n, \quad \text{if } u_s^n < 0.$$

The coefficients u_s^n and v_s^n in (11) are obtained as weighted averages of the nearest cell velocities.

5. Boundary Conditions. To find seepage velocities with (7), a knowledge of the pressure field $\phi_{i,j}^{n+\frac{1}{2}}$ is required at each cell center, including the boundary cells, which are crossed by boundary lines. For very general boundary configurations and conditions, then, the following special considerations will be applied to boundary cells.

When the pressure ϕ_s is specified as a boundary condition, the pressure $\phi_{i,j}^{n+\frac{1}{2}}$ at the boundary cell center is chosen such that a linear interpolation between it and the pressure in the nearest cell yields the boundary pressure ϕ_s . As an example, the pressure $\phi_{i,j}^{n+\frac{1}{2}}$ for the situation illustrated in Figure 2 is given by

$$(12) \quad \phi_{i,j}^{n+\frac{1}{2}} = (1-q) \phi_{i,j-1}^{n+\frac{1}{2}} + q \phi_s,$$

FIGURE 2. Boundary configuration.

where

$$q = \frac{2\Delta y}{3\Delta y - (\xi_{1-\frac{1}{2}} + \xi_{1+\frac{1}{2}})}$$

Particular care must be taken also where the normal seepage $u_{\perp}$ is prescribed on a boundary. In this connection, note that (8) can be rewritten as

$$(13) \quad u_{i+\frac{1}{2},j}^{n+1} \Delta y - u_{i-\frac{1}{2},j}^{n+1} \Delta y + v_{i,j+\frac{1}{2}}^{n+1} \Delta x - v_{i,j-\frac{1}{2}}^{n+1} \Delta x = 0,$$

which has the following physical meaning: the volume of fluid entering cell (i,j) must balance the volume of fluid leaving the cell. It is this principle which is applied to a cell crossed by the boundary. With reference to Figure 3, where $u_{\perp}$ denotes the normal velocity at which the fluid enters cell (i,j) through the boundary, the analogue of (13) in such a cell is given by

$$(14) \quad u_{i+\frac{1}{2},j}^{n+1} \xi_{i+\frac{1}{2}} - u_{i-\frac{1}{2},j}^{n+1} \xi_{i-\frac{1}{2}} + v_{i,j+\frac{1}{2}}^{n+1} \Delta x - u_{\perp}^{n+1} ((\Delta x)^2 + (\xi_{i-\frac{1}{2}} - \xi_{i+\frac{1}{2}})^2)^{\frac{1}{2}} = 0.$$

The finite difference equation for pressure in a boundary cell is obtained by substituting (9) into (14):

$$(15) \quad \eta_{i+\frac{1}{2},j} \frac{\phi_{i+\frac{1}{2},j}^{n+\frac{1}{2}} - \phi_{i,j}^{n+\frac{1}{2}}}{\Delta x} (\xi_{i+\frac{1}{2}}) - \eta_{i-\frac{1}{2},j} \frac{\phi_{i,j}^{n+\frac{1}{2}} - \phi_{i-\frac{1}{2},j}^{n+\frac{1}{2}}}{\Delta x} (\xi_{i-\frac{1}{2}}) \\ + \eta_{i,j+\frac{1}{2}} \frac{\phi_{i,j+\frac{1}{2}}^{n+\frac{1}{2}} - \phi_{i,j}^{n+\frac{1}{2}}}{\Delta y} \Delta x = \frac{F_{i+\frac{1}{2},j}^n \xi_{i+\frac{1}{2}} - F_{i-\frac{1}{2},j}^n \xi_{i-\frac{1}{2}} + G_{i,j+\frac{1}{2}}^n \Delta x}{\Delta t} \\ + u_{\perp}^{n+1} \frac{((\Delta x)^2 + (\xi_{i-\frac{1}{2}} - \xi_{i+\frac{1}{2}})^2)^{\frac{1}{2}}}{\Delta t}.$$

The set of equations (10) and (12) or (15) for the boundary cells form a linear system of equations for the unknowns $\phi_{i,j}^{n+\frac{1}{2}}$.

With regard to free surface equation (11), note that the term $\Delta h_{i+\frac{1}{2}}^n$ is always defined at the boundary except when such a boundary is an inflow boundary [2]. Hence, in this case, the free

FIGURE 3. Boundary configuration.

surface height has to be given as a function of time.

6. Stability and Accuracy Considerations. The finite difference equations (7) and (10) are second order accurate in space and first order in time, while (11) is first order accurate in space

and in time. Note that since the incompressibility conditions (8) and (14) are satisfied, the numerical scheme conserves rigorously the fluid volume in each cell.

Once the space steps Δx and Δy have been chosen, the choice of time increment Δt necessary for stability is governed by a condition for equation of motion (7) and by a surface wave Courant condition. The first constraint yields the following restriction on Δt :

$$(16) \quad \Delta t < \min \frac{2k}{\eta v} .$$

This follows directly by considering the first two equations in (4) as first order ordinary differential equations and by applying Euler's method. The surface wave Courant condition appears [3] as:

$$(17) \quad \Delta t < \frac{\Delta x}{\lambda} ,$$

where λ is the maximum wave speed and is approximated by $(gh_{\max})^{\frac{1}{2}}$.

Usually the stability condition (17) is the more restrictive. The use of implicit methods would avoid both restrictions (16) and (17). However, implicit methods tend to underestimate oscillations [12] .

7. Computer Algorithm and Examples. The algorithm for proceeding from time step t_n to time t_{n+1} can be described easily in three steps. Step 1: Determine intermediate values of seepage velocities by explicit calculations with (7), using the pressure and velocities

at t_n . Step 2: Determine the pressure field so that incompressibility condition (8) or (14) is satisfied in each cell. This stage is done iteratively by calculating a pressure change with which (8) and (14) will be satisfied and then adjusting the velocities [3]. As a starting point of the iterative procedure, the intermediate values are taken from Step 1. Step 3: Determine the new free surface positions by an explicit calculation with (11).

For the interested reader, a typical FORTRAN program is provided in the Appendix of [4].

Let us consider now a prototype, nontrivial problem of broad general interest. Consider the earth dam shown in Figure 4. The two dimensional flow domain is ABCDE. In such a domain, the fluid flow is described by system (4) and the free surface, represented by curve BC, is described by equation (5). The fluid levels d_a and d_b are fixed so that the positions of A, B, D, and E are known. The problem is to determine the free surface curve $h(x,t)$ and the point C. Thus, the problem is, in fact, a steady state problem.

As a particular case, let $d_a = 1.8$, $d_b = 0.6$, $B = (0.9, 1.8)$, $D = (3.4, 0.6)$, $E = (4.0, 0.0)$, $M = (1.0, 2.0)$, $N = (2.0, 2.0)$, $\eta = 0.1$, $\frac{\gamma}{k} = g = 1.0$. At $t_0 = 0$, the initial velocity components are $u_0 = v_0 = 0$. The boundary conditions are

$$\begin{aligned} \phi &= 0 && , \text{ on } BCD \\ \phi &= g(d_a - y) && , \text{ on } AB \\ \phi &= g(d_b - y) && , \text{ on } DE \\ v &= 0 && , \text{ on } AE. \end{aligned}$$

FIGURE 4. Schematic diagram of an earth dam configuration.

Since the boundary AB will be an inflow boundary while CDE will be an outflow boundary, the boundary condition for free surface equation (5) is given simply by

$$h(\bar{x}, t) = d_a, \quad 0 \leq t.$$

The numerical method was applied with $\Delta x = 0.1$ and $\Delta y = 0.2$, and by enclosing the configuration in a rectangle with vertices (0,0), (4,0), (4,2.6), (0,2.6), which yields a grid of 40 by 13

cells. The time step was $\Delta t = 0.05$. In our first example the initial guess of the free surface is a straight line from B to D. Whenever the method yielded an h which was above boundary segment NE, the value of h was reset to the height of NE at the same x value, which is physically correct. Figure 5 shows the free surface positions at the times $t = 0, 1, 2, 3, 10$. At $t = 10$, the free surface was no longer changing, and is, then, the desired steady state solution. In our second example, the initial free surface configuration is the horizontal straight line through B. Figure 6 shows the free surface positions, again, at times $t = 0, 1, 2, 3, 10$. As expected, the steady state configuration at $t = 10$ is identical with that of the first example.

The running time on the IBM-370 at the University of Texas for each example described above was only 1 minute 25 seconds.

A variety of computer examples for simpler problems, in which the sides of the dam were vertical, yielded results which were identical to those which had been obtained previously by others [1].

FIGURE 5

FIGURE 6

References

1. O. Baiocchi, V. Comincioli, E. Magenes, and G. A. Pozzi, "Free boundary problems in the theory of fluid flow through porous media: Existence and uniqueness theorems", *Ann. Mat. Pura Appl.*, XCVII, 1973, pp 1-82.
2. U. Bulgarelli, V. Casulli, and D. Greenspan, "On numerical treatment of free surfaces for incompressible fluid-flow problems", *Nonlinear Analysis*, 4, 1980, pp 975-983.
3. V. Casulli, "Numerical simulation of free surface thermally-influenced flows for nonhomogeneous fluids", TR 141, Dept. Math., Univ. Texas at Arlington, Arlington, Texas, 1980.
4. V. Casulli and D. Greenspan, "Numerical solution of free surface, porous flow problems", TR 146, Dept. Math., Univ. Texas at Arlington, Arlington, Texas, 1981.
5. C. W. Cryer, "A survey of steady-state porous flow free boundary problems", TR 1657, Math. Res. Ctr., Univ. Wis., Madison, Wis., 1976.
6. R. Courant, E. Isaacson, and M. Rees, "On the solution of nonlinear hyperbolic differential equations by finite differences", *Comm. Pure Appl. Math.*, 5, 1952, pp 243-255.
7. G. Fairweather, "On the approximate solution of diffusion problems by Galerkin methods", *J. Inst. Math. Appl.*, 24, 1979, pp 121-137.
8. D. Greenspan, "New mathematical models of porous flow", *Appl. Math. Modelling*, 4, 1980, pp 95-100.
9. P. Ya Polubarinova-Kochina, *THE THEORY OF GROUNDWATER MOVEMENT*, Princeton Univ. Press, Princeton, N.J., 1962.
10. D. Potter, *COMPUTATIONAL PHYSICS*, Wiley, N.Y., 1973.

11. I. Remson, G. M. Hornberger, and F. J. Molz, NUMERICAL METHODS IN SUBSURFACE HYDROLOGY, Wiley, N.Y., 1971.
12. D.-P. Wang and D. W. Kravitz, "A semi-implicit two-dimensional model of estuarine circulation", J. Phys. Oceanography, 10, 1980, pp 441-454.
13. J. E. Welch, F. H. Harlow, J. P. Shannon, and B. J. Daly, "The MAC method", TR LA 3425, Los Alamos Sci. Lab., Los Alamos, N.M., 1965.
14. C.-S. Yih, STRATIFIED FLOWS, Academic Press, N.Y., 1980.

Porous Flow FORTRAN Program

```

DIMENSION U(42,22),V(42,22),UN(42,22),VN(42,22),P(42,22),
1 JT(42),H(42),HN(42)

```

```

REAL NU

```

```

INTEGER CYCLE

```

```

READ 2,IMAX,JMAX,IL,IR,DETX,DELY,DELT

```

```

READ 3,NU,POR,HL,HR,UZERO,VZERO,GX,GY

```

```

PRINT 4,IMAX,JMAX,IL,IR,DETX,DELY,DELT

```

```

1 ,NU,POR,HL,HR,UZERO,VZERO,GX,GY

```

```

CNPRT=20

```

```

TWFIN=10.

```

```

EPSI=0.001

```

```

ONG=1.7

```

C
C
C

```

COMPUTE CONSTANT TERMS AND INITIALIZE NECESSARY VARIABLES

```

```

IM1=IMAX-1

```

```

JM1=JMAX-1

```

```

RDX=1.0/DETX

```

```

RDY=1.0/DELY

```

```

T=0.0

```

```

ITER =0

```

```

CYCLE=0.

```

```

TWPR=CNPRT*DELT

```

```

BETA=ONG/(2.*POR*DELT*(RDX**2+RDY**2))

```

```

DO 1 I=1,IMAX

```

```

DO 1 J=1,JMAX

```

```

U(I,J)=UZERO

```

```

V(I,J)=VZERO

```

```

P(I,J)=0.

```

```

1 CONTINUE

```

C
C
C

```

COMPUTE INITIAL TOP CONFIGURATION

```

```

H(1)=0.

```

```

DO 260 I=2,IMAX

```

```

IF(I.LE.IL)H(I)=HL*(I-1)/(IL-1)

```

```

IF(I.GT.IL)H(I)=HL

```

```

HM=HR-HR*(I-IR)/(IM1-IR)

```

```

IF(H(I).GT.HM)H(I)=HM

```

```

JT(I)=INT(0.5*(H(I)+H(I-1))*RDY+1.E-8)+2

```

```

260 CONTINUE

```

```

JT(1)=JT(2)

```

```

ASSIGN 4200 TO KRET

```

```

GO TO 2000

```

C
C
C

```

START CYCLE

```

```

1000 CONTINUE

```

```

ITER=0

```

```

FLG=1.

```

```

ASSIGN 3000 TO KRET

```

C
C
C

```

COMPUTE TEMPORARY U AND V

```

```

DO 1100 I=1,IM1

```

```

JT1=JT(I)
DO 1100 J=2,JT1
U(I,J)=UN(I,J)+DELT*((P(I,J)-P(I+1,J))*RDX+GX-NU*UN(I,J))*POR
V(I,J)=VN(I,J)+DELT*((P(I,J)-P(I,J+1))*RDY+GY-NU*VN(I,J))*POR

```

```
1000 CONTINUE
```

```
2000 CONTINUE
```

```
SET BOUNDARY CONDITIONS
```

```
DO 2200 I=2,IM1
```

```
JT1=JT(I)
```

```
P(I,JT1+1)=0.
```

```
IF(I.EQ.IB)P(I,JT1+1)=-GY*(HR-0.5*(H(I)+H(I-1)))
```

```
IF(I.LE.IL)P(I,JT1+1)=-GY*(HL-0.5*(H(I)+H(I-1)))
```

```
2200 CONTINUE
```

```
DO 2620 I=2,IM1
```

```
JT1=JT(I)
```

```
IF(JT(I+1).LT.JT(I);U(I,JT1)=U(I,JT1-1)
```

```
V(I,JT1)=V(I,JT1-1)
```

```
U(I,JT1+1)=U(I,JT1)
```

```
V(I,1)=0.
```

```
2620 CONTINUE
```

```
GO TO NEXT,(3000,4280)
```

```
HAS CONVERGENCE BEEN REACHED
```

```
3000 CONTINUE
```

```
IF(FLG.EQ.0.)GO TO 4000
```

```
ITER=ITER+1
```

```
IF(ITER.LT.500)GO TO 3050
```

```
I=1,N+1
```

```
GO TO 4000
```

```
3050 FLG=0.0
```

```
COMPUTE UPDATED CELL PRESSURE AND VELOCITIES
```

```
DO 3500 I=2,IM1
```

```
JT1=JT(I)
```

```
DO 3500 J=2,JT1
```

```
IF(J.EQ.JT1)GO TO 3100
```

```
D=RDY*(U(I,J)-U(I-1,J))+RDY*(V(I,J)-V(I,J-1))
```

```
IF(ABS(D).GE.NPSI)FLG=1.
```

```
DELP=-DELT*D
```

```
GO TO 3300
```

```
3100 CONTINUE
```

```
PETA=DELT/(0.5*(HN(I)+HN(I-1))-(FLOAT(JT1)-2.5)*DELT)
```

```
DELP=(1.0-PETA)*P(I,J-1)-P(I,J)+PETA*P(I,J+1)
```

```
IF(J.EQ.2)GO TO 3300
```

```
IF(I.EQ.IL)DELP=-GY*(HL-DELT/2.)-P(I,J)
```

```
IF(I.GT.IB)DELP=-GY*(HR-DELT/2.)-P(I,J)
```

```
3300 P(I,J)=P(I,J)+DELP
```

```
U(I,J)=U(I,J)+DELT*RDX*DELP*POR
```

```
U(I-1,J)=U(I-1,J)-DELT*RDX*DELP*POR
```

```
V(I,J)=V(I,J)+DELT*RDY*DELP*POR
```

```
V(I,J-1)=V(I,J-1)-DELT*RDY*DELP*POR
```

```
3500 CONTINUE
```

```
GO TO 2000
```

```
4000 CONTINUE
```

```
COMPUTE NEW SURFACE POSITION
```

```

ILP
DO 4100 I=ILP,IR
JT1=INT (HN (I) *RDY+1E-8) +2
JR1=JT(I)

```

```

VV=HV* (VN (I,JR1) +VN (I+1,JS1) ) + (0.5-HV) * (VN (I,JT1-1) +VN (I+1,JT1-1) )
IF (UU.EQ.0.) HX=0.
IF (UU.GT.0.) HX= (HN (I) -HN (I-1) ) *RDX
IF (UU.LT.0.) HX= (HN (I+1) -HN (I) ) *RDX
H (I) =HN (I) +DELT* (VV-UU*HX) /FOR
HN=HN-HAT* (X-1H) / (INT-1H)
IF (H (I) .GT.HM) H (I) =HM
JT (I) =INT (0.5* (H (I) +H (I-1) ) *RDY+1.E-8) +2

```

4100 CONTINUE

ENSION 4250 TO 4400

GO TO 2000

4250 CONTINUE

C

C

LIST VELOCITY, PRESSURE, AND SURFACE POSITION

C

5500 CONTINUE

IF (CYCLE.EQ.0) GO TO 5500

IF (T+1.E-3.LT.TWPT) GO TO 6000

TWPT=TWPT+CWPRT*DELT

5800 CONTINUE

PRINT 49,ITER,T,CYCLE

PRINT 47

DO 5900 I=1,IMAX

JT1=JT(I)

JT2=JT(I)+1

DO 5900 J=1,JT2

PRINT 48,I,J,U(I,J),V(I,J),P(I,J),H(I),JT1

5900 CONTINUE

C

C

SET THE ADVANCE TIME VELOCITIES U AND V INTO THE UN AND VN ARRAYS
AND THE ADVANCED TIME SURFACE HEIGHT H INTO THE HN ARRAY

C

6000 CONTINUE

IF (T.GT.TWPT) STOP

DO 6100 I=1,IMAX

HN(I)=H(I)

DO 6100 J=1,JMAX

UN(I,J)=U(I,J)

VN(I,J)=V(I,J)

6100 CONTINUE

C

C

ADVANCE TIME T=T+DELT

C

T=T+DELT

CYCLE=CYCLE+1

GO TO 1000

FORMAT(4I10,3F10.5)

FORMAT(8F10.5)

FORMAT(1H1,' DAT1 : ',4I5,(/,F5.2))

47 FORMAT(/,3X,'I',2X,'J',12X,'U',17X,'V',18X,'P',18X,'H',11X,'S')

48 FORMAT(1X,I3,I3,4(6X,1PE12.5),6X,I4)

49 FORMAT(1H1,'ITER= ',I5,10X,'TIME= ',1PE12.5,10X,'CYCLE= ',I4)

END